

2D Omni-Directional Barcode Scanner

□M/N: OCBS -T207□

سمات:

Support Multiple kinds of 1D and 2D barcodes;
4mil scanning resolution;
480*640 CMOS Sensor;
Easy to scan screen barcodes.

تخصيص

عام	
نموذج	OCBS -T207
اللون	orange+أسود/blue+أسود/red+black for optional
IP grade	IP52
مادة	ABS+PC
Processor	32-bit ARM MCU
واجهه المستخدم	USB
Invoices	الدعم
مؤشر	Buzzer+Lamp indicator□فاد□
مزود الطاقة	DC 5V ±5%
Electric current	200mA□231□تعليقmA□290□عملmA□أقصى□
استهلاك الطاقة	1.0W□1.16□تعليقW□1.45□عملW□أقصى□
لغة	AmericanEnglish;Belgium;Brazil;Canada (French);Denmark;Finland,(Swedish);TheFrench;Germany/Austria;Greece;Hungary;Israel (Hebrew);Italy;LatinAmerica;Dutch (Dutch);Norway;Poland;Portugal;Romania;Russia;Spain;Sweden;Switzerland(German);TurkeyF;TurkeyQ;The UK;Japan [support virtual keyboard]
OS Support	Linux□ماك□.10□.8□.7□بي□وويندوز□إكس بي□
Electrostatic Protection	15KVair charging
Shock Resistance	Drop Test 1.2m□ concrete surface□
أداء	
المستشعر	CMOS sensor
Moving Tolerance	25cm/sec(10mil QR code)
Reading Angles	Roll360°, Pitch45°,Yew60°
Scanning Angles	32°* 30°
التباين	≥30%
Ambient light illumination	0~100000LUX
نسبة الخطأ	1/500Million
Reading Mode	صورة
وضع الزناد	Auto-Sensing
دقة	Code39 4mil
Scanning Depth	Code39 4.17mil□15 bytes□□ 7cm - 13cm Code39 10.83mil□16 bytes□□8cm - 15cm Data Matrix 10.83mil□8 bytes□□ 6cm - 11cm Code QR 10.83mil□8 bytes□□ 5cm - 13cm
Decoding ability	1D:Code 128, EAN-8,Code 39,EAN-13,UPC-E0,Code 93, UPC-E1,UPC-A, Plessey, Interleaved 2 of 5, Industrial 25, Standard 25, Codabar, MSI-Plessey, UPCE0/E1, GS1-128, GS1 Databar, Matrix 2 of 5,ITF-14, Code32,Code 11,ISBN, ISSN,Standard 25, 2D:Data Matrix ,QR,PDF417

بدني	
وزن	Gross:200g
طرد	190*180*123mm
20 in 1 carton	645*390*400mm/11.3kg
بيئة	
درجة حرارة العمل والرطوبة	0 to 45 degrees centigrade, 10%~80% No condensation
درجة حرارة التخزين والرطوبة	-20 to 60 degrees centigrade , 10%~90% No condensation





OCBS-T207





OCBS-T207





OCBS-T207





OCBS-T207





OCBS-T207





OCBS-T207

