

# 20X2Characters Double Line VFD

(Model: VFD220C)

## Features:

- Supports Doublelines 20 \* 2 VFD
- Supports 26 characters
- Supports 16-bit characters
- Supports 360 characters
- Supports ESC / POS / CD5220
- Supports 3 characters

## Specifications:

- Supports 9 characters
- Supports 20 characters, 40 characters
- Supports 20 characters, 40 characters
- Supports 20 characters, 40 characters
- Supports Easyprogramming, Escape
- Supports Aedex, Epson, DSP800
- Supports 20 characters, 40 characters
- Supports 20 characters
- Supports Powermay, 20 characters, 40 characters
- Supports 20 characters, 40 characters

Character set	ASCII / Unicode / ...
Character size	24 * 8
Character height	24 * 8
Character width	24 * 8
Character depth	700cd / 2
Character color	96 characters, 26 * 26
Character font	5X7 characters
Character pitch	6.75 * 3.75 * 0.8
Character spacing	0.8 * 0.55
Character resolution	20 characters, 40 characters
Character temperature	-5 ~ 60
Character voltage	204 (V) 40 * (V) 67 * (V)
Character current	188 (L) * 40
Character power	350 characters, 0.9
Character interface	ESC / POS / CD5220 / DSP800 / UTC .....
Character compatibility	Supports 20 characters, 40 characters, 26 * 26, 5X7, 6.75 * 3.75 * 0.8, 0.8 * 0.55, 700cd / 2, 96 characters, 26 * 26, 204 (V) 40 * (V) 67 * (V), 188 (L) * 40, 350 characters, 0.9, ESC / POS / CD5220 / DSP800 / UTC .....
Character protocol	RS232 (C) 40 * (C) 67 * (C)
Character baud rate	2400/9600
MTBF	40000

□□□□□ □□□□

DC5V 1A

□□□□□

CE □ ROHS □ FCC



# VFD220C



[www.ocominc.com](http://www.ocominc.com)

CE FCC

