

# RF433 MHz Wireless/USB Cable Portable Stocktaking Terminal

(Model No.: OCBS-D007/ OCBS-D107)

## FEATURE:

- Suitable for overall process of the commodity circulation including receiving, shipping, stocktaking, loss report, replenishment etc;
- Support product information download, automatically matches products and show product name after scanned the barcode;
- Wireless Version: wireless and storage technology, no restriction of distance;
- 2.8 inches color display, menu with image for easy operation;
- 2800mA super capacity battery ensures long working time;



## SPECIFICATION:

Performance Characteristics	
Light source	650nm laser
Scan Model	Single line
Scan width & field	220mm/0~250mm (0.33mm, PCS 90%)
Interface	Standard configuration mini USB receiver; RS232 and PS2 optional
Scan rate	48±2 scan/second
Error Rate	1/5,000,000
Working way	triggered or automatic (continuous mode) scanning
Scan angle	Pitch 30°/ Roll 65°/Yaw 55°
Supported barcodes	EAN-8,EAN-13,UPC-A,UPC-E,Code 39,Code 93,Code 128,EAN128,Codaber, Industoal 2of 5,Interleave 2of5,Matrix 2of5, MSI etc.
Indicator	Beeper, LCD display
Physical Characteristics	
Screen	2.8 inch, 10*10 lines; resolution: 320*240
Dimensions	Terminal: 160x68x29mm; Receiver: 52x20x10mm
Material	ABS+ silica
RAM	16M
Color	Black or Grey
Communication Characteristics	
Frequency	433MHZ
Modulation	GFSK
Transmission Distance	Visual straight line distance 300 meters (Max)
Transmission rate	200Kbps
Electric Characteristic	
Battery	Li-Battery (3.7V, 2800mAh)
EMI/RFI:	CE&FCC DOC compliance

Working Current	50mA
<b>Environment</b>	
Operation Temperature	0 Degree C~45 Degree C
Storage Temperature	-20 Degree C ~60 Degree C
relative humidity	5%~95% (non- condensing)
ambient brightness	Max 5,000Lux
<b>Ordering Information</b>	
OCBS-D007	433MHZ Wireless Portable Stocktaking Terminal
OCBS-D107	USB Cable Portable Stocktaking Terminal