

| | |
|-------------------------------|--|
| Model | OCBP-402DT |
| Material | Plastic housing |
| Interface | USB,USB+Bluetooth,USB+Bluetooth +WIFI, USB+LAN |
| Processor | 32 bit CPU |
| Memory | 4MB Flash Memory,320KB RAM |
| Printer Head life | 50Km |
| Power supply | Input□AC 100V-240V,50-60Hz,Output□DC 24V/2.5A |
| Accessories | Power adapter,Power cable,USB cable,Manual, outside bracket for option |
| Sensors | Label edge detection, Out of paper detection, Gap detection, Black mark detection,Cover-open detection |
| Gap height | 2mm Min |
| Black-mark height | 2mm Min |
| Font and bar-code rotation | 0°,90°,180°,270° |
| Compatible command | TSPL |
| Printing | |
| Printing method | Direct Thermal |
| Resolution | 203 DPI |
| Printing speed | 152mm /s Max |
| Printing width | 30-108mm |
| Printing length | 10-250mm |
| Barcode | |
| Bar-code | 1D bar code: Code 39, Code 93, Code 128UCC, Code 128 subsets A, B, C, Coda bar, Interleaved 2 of 5, EAN-8,EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, China POST 2D bar code:PDF417, Maxi code, Data Matrix, QR code |
| Font | 8 alpha-numeric bitmap fonts, Windows fonts are downloadable from software |
| Media | |
| Paper type | Folded paper or roll paper, die-cut label, black mark paper |
| Paper width | 30-118mm |
| Media thickness | 0.06 ~ 0.22mm |
| Physical | |
| Dimension | 220*112*102mm |
| Weight | Net: 1.02kg |
| Package box | 248*140*170mm/1.87Kg |
| 8 in 1 carton | 516*300*360mm /12.4kg |
| Environment | |
| Working temperature& humidity | 0 to 45 degrees centigrade, 10%~80% No condensation |
| Storage temperature& humidity | -20 to 60 degrees centigrade , 10%~90% No condensation |