

Fixed 1D/2D Barcode Scanner Module

(Model No.: OCBS-F2200)

FEATURE:

- High performance imaging technology;
- Omni-directional scanning, easy to scan;
- High compatibility for all major 1D and 2D symbols;
- Can read the barcode on the screen and color barcode;
- 4mil excellent scanning accuracy ;
- Multi interfaces optional;

SPECIFICATION:

Performance Characteristics

Scan performance

Sensor	CMOS
Resolution	640*480, 256 gray levels
Maximum decoding speed	13mil UPC 40cm/s
Reading angle	horizontally 50 deg; vertically 20 Deg
Precision	≥4mil
Decode capability	1D 2D
Depth of field	Code 39(5mil) □ 50mm~120mm Code 39(10mil) □ 25mm~250mm UPC/EAN (13mil) □ 20mm~320mm Data Matrix(7.5mil) □ 63mm~150mm PDF417(6.6mil) □ 62mm~145mm
Sensitivity	Inclination ±45° @0°Roll and 0°Skew Rotation ±30° @0°Pitch and 0°Skew Deflection ±45° @0°Roll and 0°Skew

Electrical

Interface	USB, RS232
Input Voltage	3.3v~5v DC
Standard Power	2.0w (400mA)
Max Power	2.5w (450mA)
DC adapter	Max 5.5V 1A
LED CLASS	Class I
EMC Test	FCC part15, IEC60825-1, EN55022 Class B

User Environment

Operate Temperature	-20 deg C ~ +60 deg C (-4 Deg F to 144 deg F)
Storage Temperature	-30 deg C ~ +70 Deg C (-22 Deg F to 158 deg F)
Humidity	5% - 95%(non- condensation)
Drop resistance:	1.5m (5.0ft) drops to concrete
Light intensity	Working: sun lights, fluorescent lights



F2200



www.ocominc.com

