

# 30x2 Characters Double Line LCD Customer Display

(ModelNo.:OCPD-LCD230C-C1)

## Features:

Supports 11 command modes included EPSON etc.

Compatible with 95 national languages;

Power supply from 5V to 24V to prevent any mindless use of improper power input;

Can show 2 lines \* 30 columns or 2 lines \* 15 Chinese;

OPOS/JPOS driver is standard.

## Data sheet:

General	Display method	TN-LCD negative display (White on the Blue background)
	characters	30 columns*2 lines or 20 Chinese*2 lines
	brightness	1200cd/m2
	Character font	16*16 dot matrix
	Character type	95 Alphanumeric 32 international characters
	Character Size	9.92(H) x 4.75(W)mm Chinese: 9.92*9.5mm
	Dot size(X*Y)	0.426(H) x 0.6(V)mm
	Window size	142.7(H) x 19.82(V)mm
	PCB Size	160(L) x 36.6(W) x 10.1(H)mm
	Weight	Approx.65.5 grams
Commands Mode	LD220 EPSON POS D101 AEDEX UTC/S UTC/P ADM788 DSP800 CD5220 EMAX LOGIC CONTROL	
Language Support	FRANCE GERMANY U.K DENMARK SWENEN ITALY SPAIN APAN NORWAY DENMARKI SLAVONIC RUSSIA Portuguese Canadian French Nordic Turkish Greek West European Latin.CP858 CP860 WCP1252 CP857 TURKISH Polish WPC1250 WPC1253 GREEK WPC1255 Hebrew WPC1251 CP866 CP852 CP737 DOS greek CP858 CP864 Arabic Farsi Iran CP936-GBK, Chinese Traditional, Chinese Simplified	
Interface	RS-232 serial or USB Virtual COM	
Connection	Baud	Direct connection 9600 or 19200 bps
Reliability	MTBF	30000 hours
Power	Consumption	5-24 VDC
Safety	EMC standards Safety standards	FCC CE ROHS

