

15-inch Touch POS terminal With Aluminum Base

(M/N:POS-1513W&POS-1513A)

Features:

Intel Celeron series and intel core I3 I5 processor for option;
Rockchip high speed RK3288 processor for option;
EMMC 8GB/16GB/32GB for option;
Hard Driver Msata SSD 64GB, SSD 128GB an 256 GB for option;
Multi-point projected capacitive touch panel;
Optional side MSR and VFD220 customer display mounted to back cover;
Ture flat and water-proof scratch-resistant surface display.

Applications:

Catering: hotel, restaurant, fast-food restaurant, coffee shop, bakery and cake shop;

Retailer: Business Street, boutique, department store, cosmetics shop and high-class barbershop;

Recreation: sauna, spa, night club, theme park, casino and point of sales for lottery ticket;

Commercial: information management terminals for parking lot, inn, aviation, subway, station and wharf.

Parameter

Model	POS-1513W	POS-1513A
Name	15.1 inch aluminium alloy touch POS terminal	
Housing	aluminium alloy shell machine body base	
Color	whole black color machine usually	
Display		
Main screen	15.1 inch touch screen monitor	
Resoluiton	1024*768	
Brightness	250cd/m ²	
View angle	Horizon: 160; Vertical :150	
Touch screen	Multi-point projected G+G capacitive touch	
Sub-display	9.7 inch display W/o touch function	
Customer display	2*20 VFD or 2*20 LCD display mounted to back cover for option	
Performance		

Motherboard	Intel Celeron Bay Trail J1900 2.0GHz usually or intel core I3 / I5 4 th generation CPU for option	Rockchip series RK3288 ,quad core 1.8G, RK3399 for option
System Memory	1*SO-DIMM DDRIII slot, support1333*/1600 4GB usually, 2GB/8GB for option	On board DDRIII 1GB,2GB,4GB for option
Storage device	Msata SSD 64GB or higer, up to 256GB	on board8GB,16GB ,32GB EMMC for option
Audio	On board Real Tek ALC662	on board Real Tek ALC5640 audio chip
LAN	10/100Mbs,Realtek RTL8111F Lan chip built in Mini PCI-E slot,support embedded WIFI module	10/100Mbs,Realtek RTL8111F Lan chip Support Wi-Fi 802.11b/g/n,BT3.0/BT4.0 support
Operating System	Windows7/8/10, Embedded,WEPOS,Linux	Up to Android 8.1
Connectivity		
External I/O port(J1900/RK3288)	power button*1	
	12V DC in jack*1	
	LAN:RJ-45*1	
	USB*4	
External I/O port J1900	15PIN D-sub VGA *1	
	HDMI*1 or RS 232*1 for option	
	line out*1,MIC in*1	
External I/O port RK3288	Audio out*1	
	TF card port*1	
	RJ11 for cash drawer*1	
	RS 232*1	
Options		
MSR	optional side MSR	
Environment		
Operating temperature	0 to 40 degrees centigrade	
Storage temperature	-10 to 60 degrees centigrade	
Working humidity	10%~80% No condensation	
Storage humidity	10%~90% No condensation	
Package		
Weight	Net 5.5Kg, Gross 7.0Kg	
Package with foam inside	440*290*425mm	
Accessories		
Power adapter	110-240V/50-60HZ AC power input ,DC12V/5A output adaptor	
Power cable	Power cable plug compatible with USA /EU / UK etc and customized available	
Other		
Compliance	FCC Class A/CE Mark/LVD/CCC	







POS-1513









POS-1513







POS-1513

