

15.6 or 15.1 Inch Andorid/Windows All-in-one Touch Screen POS Machine with Printer

(M/N:POS-G156/G151)

OCOM G series pos integrated high speed thermal printer inside, R&D team take time study and research to choose each materials carefully to ensure the machine work more stably and reliably, rich IO interface make a lot of connectivities available, fashionable appearance and easily maintain and flexibly be upgraded by customers. It is the best choice for many application sites such as retaurants, coffee shops, retail stores etc...

Features:

Intel Celeron series and intel core I3 I5 processor for optional;

Hard Driver Msata SSD 64GB ,SSD 128GB an 256 GB for optional;

58mm and 80mm high speed thermal printer built in for optional;

Multi-point projected capacitive touch panel;

Optional side MSR and VFD220 customer display mounted to back cover;

Ture flat and water-proof scratch-resistant surface display.

Specification

Model	POS-G156W/A	POS-G151W/A
Name	15.6 inch all in one touch screen pos terminal	15.1 inch all in one touch screen pos terminal
Housing	plastic with metal combined	
Color	whole pearl white machine body or pearl white match gray machine body	
Display		
Main screen	15.6 inch touch screen monitor	15.1 inch touch screen monitor
Resolution	1366*768	1024*768
Brightness	250cd/m2	
View angle	Horizon: 160; Vertical :150	
Touch screen	Multi-point projected G+G capacitive touch	
Sub-display	15.6inch display and 13.3 inch display W/ or W/o touch function, resolution 1366*768 for option	151inch display W/ or W/o touch function, resolution 1024*768
Customer display	2*20 VFD mounted to back cover for option	
Performance		
Windows J1900	Motherboard	Intel Celeron Bay Trail J1900 2.0GHz or intel core I3 / I5 4th generation CPU for option
	System Memory	1*SO-DIMM DDRIII slot, support1333*/1600 4GB (default) 2GB/8GB for option
	Storage device	Msata SSD 64GB or higer, up to 256GB
	Audio	On board Real Tek ALC662 audio chip
	LAN	10/100Mbs,Realtek RTL8111F Lan chip built in Mini PCI-E slot,support embedded WIFI module
	Operating System	Windows7/8/10, Embedded,WEPOS,Linux

Android RK3288	Motherboard	Rockchip series RK3288 ,quad core 1.8G, RK3399 for option
	System Memory	On board DDRIII 2GB,4GB for option
	Storage device	on board16GB EMMC,32GB for option
	Audio	on board Real Tek ALC5640 audio chip
	LAN	10/100Mbs,Realtek RTL8111F Lan chip
	WIFI&BT module	Support Wi-Fi 802.11b/g/n,BT3.0/BT4.0 support
	Operating System	Android 7.1
Connectivity		
Windows and Android(J1900&RK3288)	power button*1	
	12V DC in jack*1	
	COM(RS232) * 1	
	LAN:RJ-45*1	
	USB *5	
	MIC in*1 , Audio out*1	
Windows (J1900)	LPT *1	
	VGA(15Pin D-sub)*1	
	RJ11 for Cash drawer *1 (optional)	
	PS/2 *1 for mouse and keyboard	
Android (RK3288)	on board RJ11 for Cash drawer *1 ,RJ11 from printer port for cash drawer*1(optional)	
	TFcard slot*1	
Options		
80mm thermal printer	direct thermal printing	
	150mm/s printing speed	
	79.5-/+ 0.5mm paper width and printable width 72mm	
	with auto cutter function and thermal head life 100km	
	USB communication	
58mm thermal printer	direct thermal printing	
	80mm/s printing speed	
	57.5-/+ 0.5mm paper width and printable width 48mm	
	thermal head life 50km	
	LPT communication	
MSR	optional side MSR just for 15.6inch	
Web camera	web camera mounted on top of the display for option	
Speaker	8Ohm/5W speaker inside for option	
Package	package	
Weight	Net 6.5Kg, Gross 8.5Kg for 15.6 dual screen	
Package with foam inside	300*465*500mm	
Environment		
Operating temperature	0 to 40 degrees centigrade	
Storage temperature	-10 to 60 degrees centigrade	
Working humidity	10%~80%	
Storage humidity	10%~90%	
Accessories		
Power adapter	110-240V/50-60HZ AC powerinput ,DC12/5A output adaptor for W/o printer and W/ 58mm printer machine DC12V/7A out put adaptor only for W/80mm printer machine	
Power cable	Power cable plug compatible with USA /EU / UK etc and customized available	
CD driver	Motherboard driver and touch driver inside for option	
Other		
Compliance	FCC Class A/CE Mark/LVD/CCC	

All In One Touch Screen POS System



Product Display

The whole machine featured anti-static protection, stronger EMI anti-interference, anti-ESD up to 8KV



Accessories



Thermal Printer



Barcode Scanner



Cash Drawer



Card Reader



Product
Accessories

SUPPORT SYSTEMS



WINDOWS



ANDROID



LINUX

Product Interface

Windows interfaces J1900



DC




LPT




COM



VGA



LAN



RJ11(optional)



USB 3.0*1



USB 2.0*4



PS/2



MIC-IN



LIN-OUT


Windows interfaces i3/i5




DC




HDMI



VGA



LAN



RJ11(optional)



USB 2.0*4



USB 3.0*1



MIC-IN




LIN-OUT

Android interfaces RK3288



DC



COM



LAN



RJ11(optional)*2



USB 3.0*1



USB 2.0*4



TF Card



MIC-IN



LIN-OUT

Screen Size



↙↘ 15.6 inch

or



↙↘ 15.6 inch

+

15.6 inch

13.3 inch

2*20 VFD



↙↘ 15.1 inch

or



↙↘ 15.1 inch

+

15.1 inch

2*20 VFD

Product Color



Product Details





Package

