

VFD CustomerDisplay

(M/N:VFD220B)

Features:

- | Supports 11 command modes included EPSON etc.
- | Powersupply from 5V to 24V to prevent any mindless use of improper power input.
- | 20-column x 2-line dot matrix in a wide viewing angle.
- | Easy connectivity to a wide range of POS products.
- | OPOS/JPOS driver is standard.

Specification

	Display Method	Vacuum Fluorescent Display (Blue-green)
	Number of characters	40(20 columns x 2 lines)
	Brightness	500~1000 cd/m ²
	Character font	5 x 7 dot matrix
	Character type	95 Alphanumeric, 32 International Characters
	Character size	9.02(H) x 5.25(W) mm
	Dot Size (X x Y)	0.86 x 1.05mm
General	Download characters	9 characters
	Panel Dimension	200(W) x 77.5(D) x 31(H)mm
	Pole Dimension	Per support length: 140(L) x 34.5(Dia)mm
	Base Dimension	169.5(W) x 98.5(D) x 39(H)mm
	Viewing Angle	Max. 90°
	Horizontal Rotation	Max. 355°
	Weight	Approx. 980 grams
Commands Mode		LD220, EPSON POS D101, AEDEX, UTC/S, UTC/P, ADM788, DSP800, CD5220, EMAX, LOGIC CONTROL
Language Support		FRANCE □ GERMANY □ U.K □ DENMARK □ SWEDEN □ ITALY □ SPAIN □ JAPAN □ NORWAY □ DENMARK II □ SLAVONIC □ RUSSIA □ Portuguese □ Canadian French □ Nordic □ Turkish □ Greek □ West European Latin
Interface		RS-232(serial) / USB
Connection	Baud rate	Direct connection 9600 or 19,200 bps
Reliability	MTBF	30,000 hours
Power	Consumption	5~24 VDC
Safety	EMC standards Safety standards	FCC, CE

